



Contour Covelight Slim

Low-profile outdoor and indoor linear lighting

Features

Dimensions L x W x H	1168 x 23 x 9 mm
Lumens per fixture	970
Color temperature (nominal)	5000 K
Color Rendering Index (CRI)	70 (nominal)
Estimated product lifetime	50.000 hours (L70)
Operating temperature	-40 °C to +70 °C
Protection class	IP66 & IP68
Special feature	Cuttable every 150 mm for two usable sides
Power	7.7 W per meter, 9.0 W per section
Efficacy	108 lm/W
Fastening	Peel-n-stick or mounting clips 4 included with each unit
Power capacity	6 units per 60 W 12 VDC power supply

¹ IP66 & IP68 ratings provide protection for extreme outdoor and wet applications or harsh weather exposure. Do not mount in a submerged application.

Benefits

- + Covelight Slim is now 34% brighter
- + Can be cut in the field
- + Quick and easy to install
- + Slim, lightweight, and low-profile fixture
- + Illuminates awnings evenly

Ordering Information

Article number	Nomenclature
16403	Contour Covelight Slim - 3500 K - 1170 x 20 x 10mm - 9 Watt - 825 lumen
14149	Contour Covelight Slim - 5000 K - 1170 x 20 x 10mm - 9 Watt - 970 lumen

Accessoires

Article number	Nomenclature
14213	Contour Covelight Slim mounting clin
16072	Contour Power Supply 12 Volt DC - 60 Watt - IP6

