



Contour **Redbar** Lighting Assembly

Features

| | |
|--------------------------|--|
| Lengths | 2.72 m 1.34 m |
| Width | 180.5 mm |
| Height | 96.5 mm |
| Temperature range | -40 °C to +70 °C |
| Supply voltage | DC 12 V |
| Power required per meter | 4,8 W |
| Colours | Red with 2700 K white backlighting |
| Efficacy | 109 lm/W |
| Power supply. | 12 V 60 W Power supply, UL recognized |
| Power capacity | 11 m 60 W 12 VDC power supply |
| Mounting | Bracket assembly |

Ordering Information

| Article number | Nomenclature |
|----------------|-----------------------------|
| 15317 | Contour Redbar 4.0 - 1,4 m. |
| 15318 | Contour Redbar 4.0 - 2,7 m. |

Accessoires

| Article number | Nomenclature |
|----------------|--|
| 16072 | Contour Power Supply 12 Volt DC - 60 Watt - IP68 |
| 15243 | Contour RedBar Install Kit (4 end caps / 1 glue) |
| 15242 | Contour RED Bar Brackets |
| 10046 | Contour 30 mtr (100ft) Belden Jacketed PLCC Cable (18 AWG) |
| 11631 | Scotchlok connector 314 bleu |