



EOS


Package overview



Package overview

The Luci Series LED Under Canopy Illumination fixture is complete, even in its standard version.

STANDARD



Set light level

- Set output percentage

Dimming

- Use PIR
- Time to dim
- Dim saving (in %)

Basic statistics

- Total power consumption
- Kwh saved

Self-controlled operating conditions

- Luminaire Intelligent Protection System (LIPS)
- Active Overheat Protection (AOP)
- Light Normalizer – No Lumen drop during lifetime

Package summary:

PACKAGE	STANDARD	PREMIUM	SENSOR SHARING	BRIDGE CONNECT	DATA EXPORT	EMERGENCY LIGHTING
Set Light Level	✓	✓	✓	✓	✓	✓
Dimming	✓	✓	✓	✓	✓	✓
Basic statistics	✓	✓	✓	✓	✓	✓
Deep-dimming		✓				
DLS (Luci)		✓				
Night-time dimming (Ambiente)		✓				
Attended timeout		✓				
Detailed statistics		✓				
Share/Use motion/ Light without Bridge			✓			
Share/Use motion/ Light/Level with Bridge				✓		
Export statistics to mail/disk					✓	
Adjustable and flexible emergency lighting						✓

Minimum EOS Manager level required:	Basic	Advanced	Advanced	Advanced	Advanced	Expert
-------------------------------------	-------	----------	----------	----------	----------	--------

Add **functionality** to your EOS luminaires

Combine packages to your liking and create your own, ideal operating LED lighting device with the features you want.

PREMIUM

Allows following configuration items to be set;

Deep dimming

- Use deep dimming
- Time to deep dimming
- Deep dimming percentage

Day light sensor (only Luci EOS²)

- Use DLS
- High dim above
- Low dim below
- DLS high dim percentage
- DLS low dim percentage
- DLS behaviour between thresholds

Night-time dimming (only Ambiente EOS²)

Attended timeout

Detailed statistics

→ *Advanced EOS Manager level*

SENSOR SHARING

Share and use information between EOS luminaires (Motion and Light)

→ *Advanced EOS Manager level*

BRIDGE CONNECT

Interact with an EOS Bridge;
Add devices and networks to the EOS network.

- Solution is based on client request

→ *Advanced EOS Manager level*

DATA EXPORT

Allows to view, and export all statistics

- Save as Excel compatible .csv to disk
- Send as Excel compatible .csv to email

→ *Advanced EOS Manager level*

EMERGENCY LIGHTING

Use your EOS fixture as a central emergency lighting

- Detect power cut
- Configure light level

→ *Expert EOS Manager level*



Bever Innovations B.V.

Industrieweg 32 | 4301 RS Zierikzee
The Netherlands

Tel +31(0)111 45 32 32

info@beverinnovations.com

www.beverinnovations.com