



Luci Series **Silver** Pendant

Features


Colour	Matte grey RAL 9006
Input voltage	TCI Power supply 110 - 240 V
Frequency	50 / 60 Hz
Light source wattage	8 W
Lumen output	675 lm
Light source efficacy	79 lm/W
Colour rendering index (CRI)	83
Beam angle	60°
Material	Diecast aluminium
Protection against water	IP20
Safety class	II
Protection against shock	IK02
Powerfactor (Pf)	0.6
Inrush current	20 A - 170µS
B-16A fuse	50 pcs
Operating temperature	-20° C / + 45° C
Safety norms	EN60598 / EN62031 / EN62471
EMC norms	EN55015
Weight single unit	544 gr
Expected lifetime at 25 °C (L70)	>60.000 hrs

Benefits

- + Easy installation due to ceiling plate
- + Perfectly suitable for environments where a true colour is vital (CRI 83)
- + White diffuser when light is off
- + Passive heat sink, no moving parts
- + Consistent color between each pendant
- + Incl. TCI driver
- + Warranty 5 years



Dimensions



Ordering information

Article number	Nomenclature	Wattage	Efficacy	Lumen Output	CCT	Beam Angle	CRI
Luci Series Silver Pendant							
15530	Pendant 3000K - 8W - Grey - nodim	8 W	79 lm/W	675	3.000	60°	83